

# PRODUCT DATA SHEET



## Product Description & Application

Waxity Hydraulic Oil ISO 10W is a high performance anti-wear hydraulic oil specifically formulated from selected base oils and a proprietary additive system to provide well balanced performance in a range of applications. Manufactured from a high quality of virgin base oils combined with anti-wear additives and rust inhibitors, to provide high stable premium hydraulic fluids with quality reserve for excellent performance under severe operating condition in mobile industrial service. Designed to provide easy and long-life performance. This product has inhibitors of corrosion and water displacement and it ensures the protection of the hydraulic systems.

# ISO 10W AW

Antiwear Hydraulic oil

## Features & Benefits

- Provides excellent overall performance.
- Enhanced frictional properties that aids fuel economy.
- High protection against wear ensuring maximum equipment life.
- Very good oxidation stability ensuring a long service life of the fluid.

## • Typical Characteristics

| TEST                   | METHOD      | RESULT |
|------------------------|-------------|--------|
| Appearance             | VISUAL      | C&B    |
| Density @29.5°C, gm/CC | ASTM D 4052 | 0.858  |
| Viscosity @100°C, cSt  | ASTM D 445  | 2.75   |
| Viscosity @40°C, cSt   | ASTM D 445  | 10.4   |
| Viscosity Index        | ASTM D 2270 | 105    |
| Pour Point, °C         | ASTM D 97   | -15    |
| Flash Point, °C        | ASTM D 92   | 200    |
| TBN, mgKOH/gm          | ASTM D 892  | 0.0    |

