PRODUCT DATA SHEET



Product Description & Application

Waxity high performance multi grade diesel engine Oil API CH/SF SAE 20W40 is an advanced high performance multigrade motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil. developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the below features. It gives great wear control to safe quard the motor in various atmospheric conditions and unforgiving applications, protecting the motor in cold climate fire up and warm climate conditions.



Features & Benefits

- Provides excellent overall performance.
- Enhanced frictional properties that aids fuel economy.
- · Provides exceptional cleaning power for dirty engines.
- Excellent low temperature capabilities for rapid engine protection at start-up.

Typical Characteristics

TEST	METHOD	RESULT
Appearance	VISUAL	C&B
Density @29.5°C, gm/CC	ASTM D 4052	0.881
Viscosity @100°C, cSt	ASTM D 445	14.5
Viscosity @40°C, cSt	ASTM D 445	126.4
Viscosity Index	ASTM D 2270	115
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	236
TBN, mgKOH/gm	ASTM D 892	7.2



