PRODUCT DATA SHEET

WAXITY LUBRICANT
PROTECT OUR ENGINE, SECURE OUR FUTURE...

Product Description & Application

Waxity Pumpset Oil SAE 40 API CC is a high-performance lubricant specifically formulated for diesel engine pump sets used in agricultural, industrial, and stationary applications. It combines advanced base oils with premium additives to deliver. Superior lubrication reduces friction and wear in single- and multi-cylinder engines. Thermal stability performs reliably in high-temperature conditions typical of continuous pump operation. Enhances durability and reduces maintenance frequency. Used in irrigation and water supply systems and also used in stationary engines powering generators or machinery.



Features & Benefits

- **Provide maximum protection**
- **Low emission engines and high-performance in pumpset**
- **Protection against engine wear and excellent low temperature**
- **High viscosity index oil and additives offers excellent protection to engine components.**

- **Typical Characteristics**

TEST	METHOD	RESULT
Appearance	VISUAL	C&B
Density @29.5°C, gm/CC	ASTM D 4052	0.852
Viscosity @100°C, cSt	ASTM D 445	13.90
Viscosity @40°C, cSt	ASTM D 445	105.13
Viscosity Index	ASTM D 2270	112
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	233
TBN, mgKOH/gm	ASTM D 892	5.6

care@waxitylubricant.com www.waxitylubricant.com +91 90549 30308