PRODUCT DATA SHEET



Product Description & Application

Waxity 15W-50 API SN / JASO MA2 is a synthetic blend formulated specifically for new generation higher CC fourstroke motorcycles ideal for commute or recreational riding. It offers protection, excellent superior wear oxidation resistance, and improved oil film that keeps the engine running efficiently even under highly stressed engine operating conditions. dedicated formulation ensures consistent power delivery the to motorcycle over extended periods. Under high RPM and high temperature circumstances, It has the best frictional properties for maximum power transfer, effortless shifting, and proper wet clutch protection.



Superior Motorcycle Engine Oil



- Provide maximum protection for all vehicle
- Low emission engines and high-performance vehicles
- · Protection against engine wear and excellent low temperature
- Special cleaning agents and dispersants help prevent deposit formation

Typical Characteristics

TEST	METHOD	RESULT
Appearance	VISUAL	C&B
Density @29.5°C, gm/CC	ASTM D 4052	0.860
Viscosity @100°C, cSt	ASTM D 445	18.90
Viscosity @40°C, cSt	ASTM D 445	143.10
Viscosity Index	ASTM D 2270	149
Pour Point, °C	ASTM D 97	-28
Flash Point, °C	ASTM D 92	244
TBN, mgKOH/gm	ASTM D 892	6.2



